smort^{tag}

SmartTAG S, M, L









SEGMENT LABELS WITH SMARTFLASH

KEY FEATURES


- **Flash capability** visible from up to 10 meters, configurable to customer or associate location
- Most readable segment displays
- Cost effective label with advanced functions
- Up to 10 year life time and replaceable battery cassette (no housing tampering)
- **Bi-directional** communication, mandatory for geolocation solutions
- Universal rail adaptation and patented design to attach shelf talkers

BASE SOFTWARE

- SmartFLASH Activation : indicates negative stock and / or promotions with flash
- NFC Activation : NFC-to-Web (marketing campaigns) and / or NFC-to-Product ID table (self scanning) included



SmartTAG M with SmartCLIP and a shelf-talker



Advanced Digital Features

SmartFLASH (green light indicator)	Yes (upon activation)
Contactless (NFC)	Yes (optional)
Latency / reactivity	< 4 s
ESL and system ACK	Yes
Geolocation	Yes
Full updates per hour	90 000

Merchandising accessories

Customizable frame	Snap on, to be clipped on front Customizable colour and / or printable logo
Mounting solutions	Rails, Individual attachments, delicatessen and fish mounting solutions
Shelf-Talker fixing solutions	SmartCLIP to attach shelf talkers on the side
	SmartFRAME to attach shelf talkers on the side and around the label

Software

System compatibility	Pricer Web Server R3.5 or later	Battery	
Cloud enabled	Yes		Yes, battery cassettes (CR2032)
Connectivity		Lifetime	Up to 10 years (30 min com/ day and 1300 hours of flashing /

Wireless

InfraRed PP4C / PP16

Design

	Small	Medium	Large
E2	19202-01	19302-01	19402-01
E4	19210-01	19310-01	19410-01
E5	19220-01	19320-01	19420-01
	1.9 x 1.4 x 0.4	2.8 x 1.4 x 0.4	3.6 x 1.6 x 0.4
Weight		27 g	36 g
	25 labels/box		
	Water resistant		
	+5° to +40 °		
	no yes no		no
	RoHS, WEEE		
	E4 E5	E2 19202-01 E4 19210-01 E5 19220-01 1.9 x 1.4 x 0.4 22 g 25 labels/b Water resis +5° to +40 no	E2 19202-01 19302-01 E4 19210-01 19310-01 E5 19220-01 19320-01 $1.9 \times 1.4 \times 2.8 \times 1.4 \times 0.4$ 22 g 27 g 25 labels/box Water resistant $+5^{\circ} \text{ to } +40^{\circ}$ no yes

Display

Display technology	LCD		
Display size (inch.)	1.3 x 0.8	2.1 x 0.8	2.9 x 0.9
Number of segments	172	174	184
Number of pages	32	32	32

Battery replaceable	Yes, battery cassettes (CR2032)
Lifetime	Up to 10 years (30 min com/ day and 1300 hours of flashing / year)



MarginMate Inc. 1717 McKinney Ave, Suite 700 Dallas, TX 75202

888-246-5390 info@marginmate.com www.marginmate.com